



## Micro Mini / Composite Impact Wrench - Jumbo Hammer



### PIW-0400

**1/2" Micro Mini Air Impact Wrench**  
Jumbo Hammer; Length: 109mmL;  
Weight : 1.3 Kgs



### PIW-0500

**1/2" Micro Mini Composite Air Impact Wrench**  
Jumbo Hammer; Length: 110mmL;  
Weight : 1.2 Kgs



### PIW-0600

**1/2" Micro Mini Air Impact Wrench**  
Jumbo Hammer; Length: 109mmL;  
Weight : 1.3 Kgs

| Model No. | Driver Size | Max. Torque |     | Max. Reverse Torque |     | Free Speed | Working Pressure | Air Inlet | Net Weight |     | Overall Length |     | Packing (KGs)      |
|-----------|-------------|-------------|-----|---------------------|-----|------------|------------------|-----------|------------|-----|----------------|-----|--------------------|
|           | Inch.       | Ft-lbs      | Nm  | Ft-lbs              | Nm  | RPM        | PSI              | Inch.     | lbs        | KGs | Inch.          | mm. | Pcs/Ctn/NW/GW/Cuft |
| PIW-0400  | 1/2         | 310         | 420 | 500                 | 678 | 900        | 90               | 1/4       | 2.9        | 1.3 | 4.3            | 109 | 10/CTN/14/16/1.1   |
| PIW-0500  | 1/2         | 310         | 420 | 500                 | 678 | 900        | 90               | 1/4       | 2.64       | 1.2 | 4.33           | 110 | 10/CTN/13/15/1.1   |
| PIW-0600  | 1/2         | 310         | 420 | 500                 | 678 | 900        | 90               | 1/4       | 2.9        | 1.3 | 4.3            | 109 | 10/CTN/14/16/1.1   |



## Composite Air Impact Wrench-Twin Hammer



### PIW-0700

**1/2" Composite Air Impact Wrench**  
Net Weight: 2.1 Kgs w/ Handle Exhaust



### PIW-0801

**3/8" Composite Air Impact Wrench**  
MAX. TORQUE IN REVERSE: 450 ft/lb (607Nm)

### PIW-0802

**1/2" Mini Composite Air Impact Wrench**  
MAX. TORQUE IN REVERSE: 500 ft/lb (678Nm)

### PIW-0803

**1/2" Composite Air Impact Wrench**  
MAX. TORQUE IN REVERSE: 780 ft/lb (1054Nm)

### PIW-0804

**3/4" Composite Air Impact Wrench**  
MAX. TORQUE : 1350 ft/lb (1830Nm)

| Model No. | Driver Size | Max. Torque |      | Max. Reverse Torque |      | Free Speed | Working Pressure | Air Inlet | Net Weight |      | Overall Length |     | Packing (KGs)        |
|-----------|-------------|-------------|------|---------------------|------|------------|------------------|-----------|------------|------|----------------|-----|----------------------|
|           | Inch.       | Ft-lbs      | Nm   | Ft-lbs              | Nm   | RPM        | PSI              | Inch.     | lbs        | KGs  | Inch.          | mm. | Pcs/Ctn/NW/GW/Cuft   |
| PIW-0700  | 1/2         | 600         | 810  | 780                 | 1054 | 8,000      | 90               | 1/4       | 4.6        | 2.1  | 7.4            | 187 | 10/CTN/21/24/1.5     |
| PIW-0801  | 3/8         | 400         | 542  | 450                 | 607  | 11,000     | 90               | 1/4       | 3          | 1.38 | 6.1            | 155 | 10/CTN/17/18/1.1     |
| PIW-0802  | 1/2         | 400         | 542  | 500                 | 678  | 11,000     | 90               | 1/4       | 3          | 1.38 | 6.1            | 155 | 10/CTN/17/18/1.1     |
| PIW-0803  | 1/2         | 600         | 810  | 780                 | 1054 | 8,000      | 90               | 1/4       | 4.84       | 2.2  | 7.3            | 186 | 10/CTN/22.5/14.5/1.5 |
| PIW-0804  | 3/4         | 900         | 1220 | 1350                | 1830 | 7,000      | 90               | 3/8       | 7.48       | 3.4  | 8.47           | 215 | 4/CTN/17.5/19/1.2    |