



Torque Control Air Screwdriver - Push Start & Shut Off



PCS-0101 - Rear Exhaust
Torque Control Air Screwdriver - M3.3

PCS-0104 - Rear Exhaust
Torque Control Air Screwdriver - M4.7

PCS-0102 - Rear Exhaust
Torque Control Air Screwdriver - M4.2

PCS-0105 - Rear Exhaust
Torque Control Air Screwdriver - M5.0

PCS-0103 - Rear Exhaust
Torque Control Air Screwdriver - M4.5

PCS-0106 - Rear Exhaust
Torque Control Air Screwdriver - M5.7



PCS-0201 - Rear Exhaust
Torque Control Air Screwdriver - M5.8

PCS-0203 - Rear Exhaust
Torque Control Air Screwdriver - M6.4

PCS-0202 - Rear Exhaust
Torque Control Air Screwdriver - M6.0

PCS-0204 - Rear Exhaust
Torque Control Air Screwdriver - M7.0

Model No.	Standard Deviation	Fastening Capacity		Torque Range KGF-CM	Free Speed RPM	Working Pressure PSI	Air Inlet Inch.	Net Weight		Overall Length		Packing (KGs) Pcs/Ctn/NW/GW/Cuft
		Machine	Tapping					lbs	KGs	Inch.	mm.	
PCS-0101	±3	M1.7~M3.3	M1.3~M2.7	1 ~ 8	1,000	90	1/4	1.1	0.5	7.64	194	10/CTN/6/7/0.8
PCS-0102	±3	M2.2~M4.2	M1.7~M3.2	3 ~ 17	1,800	90	1/4	1.1	0.5	7.64	194	10/CTN/6/7/0.8
PCS-0103	±3	M2.2~M4.5	M1.7~M3.5	3 ~ 20	2,200	90	1/4	1.1	0.5	7.64	194	10/CTN/6/7/0.8
PCS-0104	±3	M2.2~M4.7	M1.7~M3.8	3 ~ 25	1,800	90	1/4	1.1	0.5	7.64	194	10/CTN/6/7/0.8
PCS-0105	±3	M2.8~M5.0	M2.2~M4.0	5 ~ 30	1,000	90	1/4	1.1	0.5	7.64	194	10/CTN/6/7/0.8
PCS-0106	±3	M3.3~M5.7	M2.7~M4.4	8 ~ 40	800	90	1/4	1.1	0.5	7.64	194	10/CTN/6/7/0.8
PCS-0201	±3	M2.8~M5.8	M2.2~M4.7	5 ~ 45	1,700	90	1/4	1.83	0.83	9	228	10/CTN/10/11/0.8
PCS-0202	±3	M2.9~M6.0	M2.6~M4.9	7 ~ 50	1,400	90	1/4	1.83	0.83	9	228	10/CTN/10/11/0.8
PCS-0203	±3	M2.9~M6.4	M2.6~M5.4	7 ~ 65	1,000	90	1/4	1.83	0.83	9	228	10/CTN/10/11/0.8
PCS-0204	±3	M4.1~M7.0	M3.1~M6.0	15 ~ 95	550	90	1/4	1.83	0.83	9	228	10/CTN/10/11/0.8



Air Impact Screwdriver - Ultra Duty



PIS-0100
Air Impact Screwdriver -5H
w/ 360° Adjustable Exhaust Muffler



PIS-0200
Ultra Duty Air Impact Screwdriver-6H
w/ 360° Adjustable Exhaust Muffler



PIS-0300
Ultra Duty Air Impact Screwdriver -8H
w/ Rear Exhaust

Model No.	Hex Shank	Working Torque		Bolt Size Capacity	Free Speed RPM	Working Pressure PSI	Air Inlet Inch.	Net Weight		Overall Length		Packing (KGs) Pcs/Ctn/NW/GW/Cuft
		Ft-lbs	Nm					lbs	KGs	Inch.	mm.	
PIS-0100	1/4	28	38	M4 ~ M6	14,000	90	1/4	1.54	0.7	7.28	185	20/CTN/16.5/17.5/0.96
PIS-0200	1/4	30	40	M5 ~ M6	10,000	90	1/4	1.87	0.85	7.4	188	10/CTN/9/10.17/0.5
PIS-0300	1/4	60	81	M8	10,000	90	1/4	2.42	1.1	9.05	230	10/CTN/14/15/0.8